



SPECIFICATIONS

HOOD <ul style="list-style-type: none"> •Type 	Rear hinged, front opening type
FRONT DOOR <ul style="list-style-type: none"> •Construction •Regulator system •Locking system 	Front hinged, full door construction X-arm type Pin-fork system
REAR DOOR <ul style="list-style-type: none"> •Construction •Regulator system •Locking system 	Front hinged, full door construction X-arm type Pin-fork system
TRUNK LID (4 doors) <ul style="list-style-type: none"> •Type 	Torsion bar type
GLASS THICKNESS mm (in.) <ul style="list-style-type: none"> •Windshield glass •Front window glass •Rear fixed glass •Rear window glass 	Laminated clear, tinted 5 (0.20) 3.2 (0.13) 3.2 (0.13) 3.2 (0.13)
SEAT BELTS <ul style="list-style-type: none"> •Type 	3 point type with E.L.R (Emergency Locking Retractor).

TIGHTENING TORQUE

Items	Nm	kgf-cm	lbf-ft
Front and rear doors			
•Door hinge to body	34 ~ 42	340 ~ 420	24.5 ~ 30
•Door hinge to door	13 ~ 26	130 ~ 260	10 ~ 19
•Glass mounting bolt	8 ~ 12	80 ~ 120	6 ~ 9
•Door latch mounting screw	7 ~ 11	70 ~ 110	5 ~ 8
•Outside handle mounting bolt	7 ~ 11	70 ~ 110	5 ~ 8
•Door striker mounting bolt	17 ~ 22	170 ~ 220	12 ~ 16
•Door checker to door	7 ~ 11	70 ~ 110	5 ~ 8

Trunk lid <ul style="list-style-type: none"> •Trunk lid hinge to body •Trunk lid hinge to trunk lid •Trunk lid latch mounting bolt •Trunk lid straker mounting bolt •Key cylinder mounting nut 	<p>7 ~ 9</p> <p>7 ~ 9</p> <p>7 ~ 11</p> <p>7 ~ 11</p> <p>7 ~ 11</p>	<p>70 ~ 90</p> <p>70 ~ 90</p> <p>70 ~ 110</p> <p>70 ~ 110</p> <p>70 ~ 110</p>	<p>5 ~ 6.5</p> <p>5 ~ 6.5</p> <p>5 ~ 8</p> <p>5 ~ 8</p> <p>5 ~ 8</p>
Hood <ul style="list-style-type: none"> •Hood hinge to body •Hood hinge to hood •Hood latch to body 	<p>22 ~ 27</p> <p>22 ~ 27</p> <p>7 ~ 11</p>	<p>220 ~ 270</p> <p>220 ~ 270</p> <p>70 ~ 110</p>	<p>16 ~ 19.5</p> <p>16 ~ 19.5</p> <p>5 ~ 8.0</p>
Seat <ul style="list-style-type: none"> •Front seat to floor bolt •Rear seat back tilting bracket •Rear seat cushion mounting bolts 	<p>35 ~ 55</p> <p>17 ~ 26</p> <p>17 ~ 26</p>	<p>350 ~ 550</p> <p>170 ~ 260</p> <p>170 ~ 260</p>	<p>25.3 ~ 40</p> <p>12 ~ 19</p> <p>12 ~ 19</p>
Seat belt <ul style="list-style-type: none"> •Front seat belt buckle •Front seat belt upper anchor •Front seat belt retractor to center pillar •Front seat belt height adjuster •Rear seat belt anchor attaching bolt •Rear seat belt retractor mounting bolt 	<p>40 ~ 55</p> <p>40 ~ 55</p> <p>40 ~ 55</p> <p>40 ~ 55</p> <p>40 ~ 55</p> <p>40 ~ 55</p>	<p>400 ~ 550</p> <p>400 ~ 550</p> <p>400 ~ 550</p> <p>400 ~ 550</p> <p>400 ~ 550</p> <p>400 ~ 550</p>	<p>29 ~ 40</p> <p>29 ~ 40</p> <p>29 ~ 40</p> <p>29 ~ 40</p> <p>29 ~ 40</p> <p>29 ~ 40</p>